

4MXM80N

Heating (50Hz 230V)

Outdoor unit	Indoor unit	Heating capacity [kW]				Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Room C	Room D	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.	
4MXM80N*	1,5	1,88	---	---	---	1,25	1,88	3,87	0,29	0,51	1,13	1,33	2,34	5,19	95
	2,0	2,46	---	---	---	1,28	2,46	4,26	0,30	0,66	1,18	1,38	3,01	5,42	95
	2,5	3,08	---	---	---	1,33	3,08	4,73	0,32	0,86	1,27	1,46	3,95	5,82	95
	3,5	4,31	---	---	---	1,45	4,31	5,31	0,33	1,39	1,68	1,51	6,37	7,68	95
	4,2	---	5,18	---	---	1,49	5,18	6,16	0,34	1,63	1,90	1,55	7,45	8,70	95
	5,0	---	6,15	---	---	1,86	6,15	7,40	0,43	1,74	2,18	1,95	7,99	9,99	95
	6,0	---	7,38	---	---	2,15	7,38	8,52	0,53	2,15	2,56	2,44	9,83	11,72	95
	7,1	---	8,74	---	---	2,45	8,74	9,36	0,57	2,71	2,88	2,62	12,43	13,18	95
	1,5+1,5	1,85	1,85	---	---	1,45	3,70	5,57	0,41	0,86	1,26	1,89	3,94	5,76	95
	1,5+2,0	1,84	2,46	---	---	1,51	4,30	5,57	0,41	1,01	1,26	1,89	4,63	5,76	95
	1,5+2,5	1,84	3,06	---	---	1,65	4,90	7,37	0,45	1,17	1,82	2,06	5,36	8,35	95
	1,5+3,5	1,83	4,27	---	---	1,94	6,10	7,52	0,52	1,64	2,00	2,37	7,51	9,14	95
	1,5+4,2	1,84	5,16	---	---	2,14	7,00	8,61	0,55	1,94	2,46	2,54	8,88	11,25	95
	1,5+5,0	1,85	6,15	---	---	2,38	8,00	9,07	0,50	2,11	2,32	2,28	9,66	10,63	95
	1,5+6,0	1,80	7,20	---	---	2,66	9,00	10,06	0,52	2,30	2,53	2,37	10,53	11,60	95
	1,5+7,1	1,67	7,93	---	---	2,96	9,60	10,30	0,55	2,47	2,52	2,50	11,31	11,56	95
	2,0+2,0	2,45	2,45	---	---	1,65	4,90	6,81	0,32	1,16	1,67	1,46	5,31	7,64	95
	2,0+2,5	2,44	3,06	---	---	1,80	5,50	7,12	0,35	1,34	1,75	1,59	6,14	8,00	95
	2,0+3,5	2,44	4,26	---	---	2,09	6,70	7,64	0,40	1,70	2,04	1,85	7,79	9,36	95
	2,0+4,2	2,45	5,15	---	---	2,28	7,60	8,87	0,44	1,98	2,46	2,02	9,07	11,25	95
	2,0+5,0	2,43	6,07	---	---	2,52	8,50	9,07	0,52	2,28	2,32	2,37	10,44	10,63	95
	2,0+6,0	2,33	6,98	---	---	2,79	9,30	10,06	0,54	2,42	2,53	2,45	11,08	11,60	95
	2,0+7,1	2,11	7,49	---	---	3,10	9,60	10,77	0,57	2,47	2,77	2,62	11,31	12,70	95
	2,5+2,5	3,05	3,05	---	---	1,94	6,10	7,45	0,39	1,68	2,05	1,76	7,69	9,40	95
	2,5+3,5	3,04	4,26	---	---	2,23	7,30	8,87	0,52	2,02	2,56	2,37	9,25	11,73	95
	2,5+4,2	3,06	5,14	---	---	2,44	8,20	9,37	0,54	2,28	2,78	2,45	10,44	12,74	95
	2,5+5,0	3,00	6,00	---	---	2,66	9,00	9,68	0,54	2,51	2,61	2,45	11,49	11,95	95
	2,5+6,0	2,82	6,78	---	---	2,94	9,60	10,50	0,55	2,63	2,82	2,54	12,04	12,92	95
	2,5+7,1	2,50	7,10	---	---	3,23	9,60	10,77	0,59	2,50	2,81	2,71	11,45	12,87	95
	3,5+3,5	4,25	4,25	---	---	2,52	8,50	9,55	0,55	2,47	2,92	2,54	11,31	13,36	95
	3,5+4,2	4,09	4,91	---	---	2,71	9,00	10,16	0,57	2,69	3,33	2,62	12,32	15,25	95
	3,5+5,0	3,91	5,59	---	---	2,94	9,50	10,32	0,58	2,66	2,81	2,67	12,18	12,87	95
	3,5+6,0	3,54	6,06	---	---	3,21	9,60	10,75	0,57	2,48	2,78	2,62	11,36	12,74	95
	3,5+7,1	3,17	6,43	---	---	3,52	9,60	10,78	0,63	2,42	2,73	2,88	11,08	12,48	95
	4,2+4,2	4,75	4,75	---	---	2,91	9,50	9,98	0,59	2,55	2,58	2,71	11,68	11,82	95
	4,2+5,0	4,38	5,22	---	---	3,13	9,60	10,52	0,60	2,59	2,76	2,75	11,86	12,61	95
	4,2+6,0	3,95	5,65	---	---	3,41	9,60	10,76	0,61	2,39	2,73	2,80	10,94	12,48	95
	4,2+7,1	3,57	6,03	---	---	3,70	9,60	10,80	0,66	2,38	2,72	3,01	10,90	12,43	95
	5,0+5,0	4,80	4,80	---	---	3,35	9,60	10,65	0,63	2,46	2,72	2,88	11,26	12,43	95
	5,0+6,0	4,36	5,24	---	---	3,62	9,60	10,89	0,62	2,35	2,69	2,84	10,76	12,30	95

Notes

- The total capacity of each connected indoor unit is up to 14.5kW.
- The values above are for connecting with the following indoor unit types:
1.5,2.0,2.5,3.5,4.2,5.0,6.0,7.1 kW class
Wall-mounted CTXM-M,FTXM-M series
- Heating capacity conditions
Indoor temperature 20°C DB
Outdoor temperature 7°C DB / 6°C WB
- Editable data for this drawing are available in the GDE(E-BOM) system.
- For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see 3D106169.

3D105412