

## 4MXM80N

Heating (50Hz 230V)

Outdoor unit	Indoor unit	Heating capacity [kW]				Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Room C	Room D	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.	
4MXM80N*	2.0+2.5+3.5+4.2	1,57	1,97	2,75	3,30	3,96	9,60	11,17	0,62	2,24	2,60	2,84	10,26	11,91	95
	2.0+2.5+3.5+5.0	1,48	1,85	2,58	3,69	4,17	9,60	11,29	0,65	2,16	2,60	2,97	9,89	11,91	95
	2.0+2.5+3.5+6.0	1,37	1,71	2,40	4,11	4,45	9,60	11,53	0,66	2,06	2,52	3,01	9,43	11,56	95
	2.0+2.5+4.2+4.2	1,49	1,86	3,13	3,13	4,15	9,60	11,18	0,65	2,23	2,59	2,97	10,21	11,86	95
	2.0+2.5+4.2+5.0	1,40	1,75	2,94	3,50	4,37	9,60	11,30	0,67	2,15	2,60	3,05	9,84	11,91	95
	2.0+2.5+5.0+5.0	1,32	1,66	3,31	3,31	4,59	9,60	11,44	0,70	2,12	2,56	3,18	9,71	11,73	95
	2.0+3.5+3.5+3.5	1,54	2,69	2,69	2,69	4,04	9,60	11,17	0,65	2,11	2,60	2,97	9,66	11,91	95
	2.0+3.5+3.5+4.2	1,45	2,55	2,55	3,05	4,23	9,60	11,18	0,67	2,25	2,59	3,05	10,30	11,86	95
	2.0+3.5+3.5+5.0	1,37	2,40	2,40	3,43	4,45	9,60	11,30	0,70	2,16	2,60	3,18	9,89	11,91	95
	2.0+3.5+4.2+4.2	1,38	2,42	2,90	2,90	4,43	9,60	11,18	0,71	2,23	2,59	3,27	10,21	11,86	95
	2.5+2.5+2.5+2.5	2,40	2,40	2,40	2,40	3,35	9,60	11,14	0,55	2,22	2,61	2,50	10,17	11,95	95
	2.5+2.5+2.5+3.5	2,18	2,18	2,18	3,05	3,62	9,60	11,15	0,58	2,26	2,60	2,67	10,35	11,91	95
	2.5+2.5+2.5+4.2	2,05	2,05	2,05	3,45	3,81	9,60	11,16	0,60	2,25	2,60	2,75	10,30	11,91	95
	2.5+2.5+2.5+5.0	1,92	1,92	1,92	3,84	4,04	9,60	11,29	0,63	2,16	2,61	2,88	9,89	11,95	95
	2.5+2.5+2.5+6.0	1,78	1,78	1,78	4,27	4,31	9,60	11,53	0,64	2,06	2,53	2,93	9,43	11,60	95
	2.5+2.5+3.5+3.5	2,00	2,00	2,80	2,80	3,90	9,60	11,16	0,63	2,25	2,60	2,88	10,30	11,91	95
	2.5+2.5+3.5+4.2	1,89	1,89	2,65	3,17	4,09	9,60	11,17	0,65	2,23	2,60	2,97	10,21	11,91	95
	2.5+2.5+3.5+5.0	1,78	1,78	2,49	3,56	4,31	9,60	11,29	0,67	2,15	2,60	3,05	9,84	11,91	95
	2.5+2.5+3.5+6.0	1,66	1,66	2,32	3,97	4,59	9,60	11,53	0,68	2,06	2,52	3,10	9,43	11,56	95
	2.5+2.5+4.2+4.2	1,79	1,79	3,01	3,01	4,28	9,60	11,18	0,67	2,21	2,59	3,05	10,12	11,86	95
2.5+2.5+4.2+5.0	1,69	1,69	2,84	3,38	4,51	9,60	11,30	0,71	2,13	2,60	3,27	9,75	11,91	95	
2.5+3.5+3.5+3.5	1,85	2,58	2,58	2,58	4,17	9,60	11,17	0,67	2,25	2,60	3,05	10,30	11,91	95	
2.5+3.5+3.5+4.2	1,75	2,45	2,45	2,94	4,37	9,60	11,18	0,70	2,23	2,59	3,18	10,21	11,86	95	
2.5+3.5+3.5+5.0	1,66	2,32	2,32	3,31	4,59	9,60	11,30	0,71	2,15	2,60	3,27	9,84	11,91	95	
2.5+3.5+4.2+4.2	1,67	2,33	2,80	2,80	4,56	9,60	11,18	0,73	2,21	2,59	3,36	10,12	11,86	95	
3.5+3.5+3.5+3.5	2,40	2,40	2,40	2,40	4,45	9,60	11,18	0,71	2,19	2,59	3,27	10,03	11,86	95	

### Notes

1. The total capacity of each connected indoor unit is up to 14.5kW.
2. The values above are for connecting with the following indoor unit types:  
2.0,2.5,3.5,4.2,5.0,6.0 kW class  
Wall-mounted FTXM-M series
3. Heating capacity conditions  
Indoor temperature 20°C DB  
Outdoor temperature 7°C DB / 6°C WB
4. Editable data for this drawing are available in the GDE(E-BOM) system.
5. For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see 3D106169.

3D105418