

5MXM90N

Cooling (50Hz 230V)

Outdoor unit	Indoor unit	Cooling capacity [kW]					Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Room C	Room D	Room E	Min.	Nom.	Max.	Min.	Nom.	Max.	Min.	Nom.	Max.	
5MXM90N*	3.5+4.2+5.0	2,48	---	2,98	3,54	---	3,24	9,00	9,18	0,62	2,32	2,93	2,82	10,62	13,40	95
	3.5+4.2+6.0	2,30	---	2,76	3,94	---	3,39	9,00	9,50	0,65	2,29	2,99	2,99	10,49	13,69	95
	3.5+4.2+7.1	2,13	---	2,55	4,32	---	3,54	9,00	10,01	0,69	2,26	3,52	3,16	10,35	16,09	95
	3.5+5.0+5.0	2,33	---	3,33	3,33	---	3,36	9,00	9,20	0,65	2,19	2,98	2,99	10,03	13,65	95
	3.5+5.0+6.0	2,17	---	3,10	3,72	---	3,50	9,00	9,67	0,65	2,16	3,02	2,99	9,89	13,81	95
	3.5+5.0+7.1	2,02	---	2,88	4,10	---	3,66	9,00	10,14	0,69	2,14	3,48	3,16	9,80	15,93	95
	3.5+6.0+6.0	2,03	---	3,48	3,48	---	3,65	9,00	10,59	0,65	2,15	3,56	2,99	9,84	16,29	95
	4.2+4.2+4.2	3,00	---	3,00	3,00	---	3,23	9,00	9,18	0,65	2,37	2,91	2,99	10,85	13,32	95
	4.2+4.2+5.0	2,82	---	2,82	3,36	---	3,35	9,00	9,26	0,65	2,31	2,93	2,99	10,58	13,40	95
	4.2+4.2+6.0	2,63	---	2,63	3,75	---	3,48	9,00	9,51	0,65	2,28	2,99	2,99	10,44	13,69	95
	4.2+4.2+7.1	2,44	---	2,44	4,12	---	3,65	9,00	10,02	0,69	2,25	3,52	3,16	10,30	16,09	95
	4.2+5.0+5.0	2,66	---	3,17	3,17	---	3,46	9,00	9,21	0,68	2,30	2,95	3,12	10,53	13,52	95
	4.2+5.0+6.0	2,49	---	2,96	3,55	---	3,60	9,00	10,18	0,69	2,27	3,54	3,16	10,39	16,21	95
	5.0+5.0+5.0	3,00	---	3,00	3,00	---	3,57	9,00	9,98	0,69	2,29	3,62	3,16	10,49	16,58	95
	1.5+1.5+1.5+1.5	1,50	1,50	1,50	1,50	---	2,31	6,00	6,73	0,44	1,25	1,44	2,02	5,73	6,60	95
	1.5+1.5+1.5+2.0	1,50	1,50	1,50	2,00	---	2,36	6,50	7,11	0,47	1,38	1,62	2,15	6,32	7,41	95
	1.5+1.5+1.5+2.5	1,50	1,50	1,50	2,50	---	2,42	7,00	7,46	0,47	1,50	1,76	2,15	6,87	8,06	95
	1.5+1.5+1.5+3.5	1,41	1,41	1,41	3,28	---	2,55	7,50	8,12	0,50	1,63	2,06	2,27	7,46	9,45	95
	1.5+1.5+1.5+4.2	1,38	1,38	1,38	3,86	---	2,66	8,00	8,53	0,50	1,94	2,39	2,27	8,88	10,96	95
	1.5+1.5+1.5+5.0	1,26	1,26	1,26	4,21	---	2,77	8,00	8,96	0,53	1,90	2,58	2,44	8,70	11,81	95
	1.5+1.5+1.5+6.0	1,24	1,24	1,24	4,97	---	2,92	8,70	9,44	0,53	2,34	2,63	2,44	10,71	12,02	95
	1.5+1.5+1.5+7.1	1,16	1,16	1,16	5,51	---	3,08	9,00	9,86	0,56	2,39	2,88	2,57	10,94	13,20	95
	1.5+1.5+2.0+2.0	1,50	1,50	2,00	2,00	---	2,42	7,00	7,46	0,47	1,50	1,76	2,15	6,87	8,06	95
	1.5+1.5+2.0+2.5	1,50	1,50	2,00	2,50	---	2,48	7,50	7,79	0,47	1,63	1,91	2,15	7,46	8,76	95
	1.5+1.5+2.0+3.5	1,41	1,41	1,88	3,29	---	2,63	8,00	8,42	0,50	1,94	2,23	2,27	8,88	10,18	95
	1.5+1.5+2.0+4.2	1,30	1,30	1,74	3,65	---	2,73	8,00	8,80	0,53	1,94	2,56	2,44	8,88	11,73	95
	1.5+1.5+2.0+5.0	1,28	1,28	1,70	4,25	---	2,85	8,50	9,21	0,53	2,23	2,77	2,44	10,21	12,67	95
	1.5+1.5+2.0+6.0	1,23	1,23	1,64	4,91	---	2,99	9,00	9,64	0,56	2,39	2,75	2,57	10,94	12,59	95
	1.5+1.5+2.0+7.1	1,12	1,12	1,49	5,28	---	3,16	9,00	10,04	0,60	2,36	3,02	2,74	10,81	13,81	95
	1.5+1.5+2.5+2.5	1,41	1,41	2,34	2,34	---	2,55	7,50	8,12	0,50	1,63	2,06	2,27	7,46	9,45	95
	1.5+1.5+2.5+3.5	1,33	1,33	2,22	3,11	---	2,70	8,00	8,70	0,53	1,94	2,51	2,44	8,88	11,49	95
	1.5+1.5+2.5+4.2	1,31	1,31	2,19	3,68	---	2,80	8,50	9,06	0,53	2,25	2,74	2,44	10,30	12,55	95
	1.5+1.5+2.5+5.0	1,24	1,24	2,07	4,14	---	2,92	8,70	9,44	0,56	2,33	2,89	2,57	10,67	13,24	95
	1.5+1.5+2.5+6.0	1,17	1,17	1,96	4,70	---	3,07	9,00	9,83	0,56	2,43	2,88	2,57	11,13	13,20	95
	1.5+1.5+2.5+7.1	1,07	1,07	1,79	5,07	---	3,23	9,00	10,16	0,60	2,40	3,08	2,74	10,99	14,09	95
	1.5+1.5+3.5+3.5	1,28	1,28	2,98	2,98	---	2,85	8,50	9,21	0,53	2,25	2,80	2,44	10,30	12,83	95
	1.5+1.5+3.5+4.2	1,26	1,26	2,94	3,53	---	2,95	9,00	9,32	0,56	2,47	2,87	2,57	11,31	13,12	95
	1.5+1.5+3.5+5.0	1,17	1,17	2,74	3,91	---	3,07	9,00	9,68	0,59	2,40	3,02	2,69	10,99	13,81	95
	1.5+1.5+3.5+6.0	1,08	1,08	2,52	4,32	---	3,21	9,00	10,15	0,59	2,37	3,08	2,69	10,85	14,09	95
	1.5+1.5+3.5+7.1	0,99	0,99	2,32	4,70	---	3,38	9,00	10,17	0,63	2,34	3,08	2,86	10,71	14,09	95
1.5+1.5+4.2+4.2	1,18	1,18	3,32	3,32	---	3,05	9,00	9,52	0,59	2,45	2,99	2,69	11,22	13,69	95	
1.5+1.5+4.2+5.0	1,11	1,11	3,10	3,69	---	3,17	9,00	9,69	0,59	2,39	3,02	2,69	10,94	13,81	95	
1.5+1.5+4.2+6.0	1,02	1,02	2,86	4,09	---	3,32	9,00	10,16	0,60	2,36	3,08	2,74	10,81	14,09	95	
1.5+1.5+4.2+7.1	0,94	0,94	2,64	4,47	---	3,47	9,00	10,18	0,63	2,33	3,08	2,86	10,67	14,09	95	

Notes

- The total capacity of each connected indoor unit is up to 15.6kW.
- The values above are for connecting with the following indoor unit types:
1.5,2.0,2.5,3.5,4.2,5.0,6.0,7.1 kW class
Wall-mounted CTXM-M,FTXM-M series
- Cooling capacity conditions
Indoor temperature 27°C DB / 19°C WB
Outdoor temperature 35°C DB
- Editable data for this drawing are available in the GDE (E-BOM) system.
- For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see 3D106169.

D3105427