

2.2 Combination

Operation mode : Cooling

Power supply voltage : 220V

Operating status	Indoor unit				Unit capacity (kW)			Total				
	A	B	C	ΣkBTU	A	B	C	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Power factor (%)	Rated SEER
1 unit	05	-	-	5	1.50	-	-	1.50 (1.20 - 1.80)	310 (240 - 380)	1.67 (1.52 - 1.89)	84 (72 - 92)	-
	07	-	-	7	2.00	-	-	2.00 (1.30 - 2.50)	420 (240 - 590)	2.25 (1.52 - 2.93)	85 (72 - 92)	-
	10	-	-	10	2.70	-	-	2.70 (1.30 - 3.20)	640 (240 - 860)	3.40 (1.52 - 4.20)	86 (72 - 93)	-
	13	-	-	13	3.70	-	-	3.70 (1.30 - 4.10)	1050 (240 - 1190)	5.49 (1.52 - 5.80)	87 (72 - 93)	-
2 units	05	05	-	10	1.50	1.50	-	3.00 (1.60 - 4.20)	910 (290 - 1130)	4.50 (1.84 - 5.45)	92 (72 - 94)	5.10
	07	05	-	12	2.00	1.50	-	3.50 (1.60 - 4.30)	960 (290 - 1130)	4.75 (1.84 - 5.45)	92 (72 - 94)	5.64
	10	05	-	15	2.57	1.43	-	4.00 (1.60 - 4.40)	1030 (290 - 1130)	5.12 (1.84 - 5.45)	92 (72 - 94)	6.01
	13	05	-	18	2.85	1.15	-	4.00 (1.60 - 4.50)	960 (290 - 1130)	4.75 (1.84 - 5.45)	92 (72 - 94)	6.45
	07	07	-	14	2.00	2.00	-	4.00 (1.60 - 4.50)	1030 (290 - 1130)	5.12 (1.84 - 5.45)	92 (72 - 94)	6.55
	10	07	-	17	2.30	1.70	-	4.00 (1.60 - 4.60)	960 (290 - 1130)	4.75 (1.84 - 5.45)	92 (72 - 94)	6.58
	13	07	-	20	2.60	1.40	-	4.00 (1.60 - 4.70)	940 (290 - 1140)	4.65 (1.84 - 5.50)	92 (72 - 94)	6.65
	10	10	-	20	2.00	2.00	-	4.00 (1.60 - 4.70)	940 (290 - 1140)	4.65 (1.84 - 5.50)	92 (72 - 94)	6.63
	13	10	-	23	2.31	1.69	-	4.00 (1.60 - 4.80)	930 (290 - 1150)	4.59 (1.84 - 5.55)	92 (72 - 94)	6.70
	13	13	-	26	2.00	2.00	-	4.00 (1.60 - 4.90)	920 (290 - 1150)	4.55 (1.84 - 5.55)	92 (72 - 94)	6.73

Power supply voltage : 230V

Operating status	Indoor unit				Unit capacity (kW)			Total				
	A	B	C	ΣkBTU	A	B	C	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Power factor (%)	Rated SEER
1 unit	05	-	-	5	1.50	-	-	1.50 (1.20 - 1.80)	310 (240 - 380)	1.60 (1.45 - 1.80)	84 (72 - 92)	-
	07	-	-	7	2.00	-	-	2.00 (1.30 - 2.50)	420 (240 - 590)	2.15 (1.45 - 2.80)	85 (72 - 92)	-
	10	-	-	10	2.70	-	-	2.70 (1.30 - 3.20)	640 (240 - 860)	3.25 (1.45 - 4.00)	86 (72 - 93)	-
	13	-	-	13	3.70	-	-	3.70 (1.30 - 4.10)	1050 (240 - 1190)	5.25 (1.45 - 5.55)	87 (72 - 93)	-
2 units	05	05	-	10	1.50	1.50	-	3.00 (1.60 - 4.20)	910 (290 - 1130)	4.30 (1.76 - 5.23)	92 (72 - 94)	5.10
	07	05	-	12	2.00	1.50	-	3.50 (1.60 - 4.30)	960 (290 - 1130)	4.55 (1.76 - 5.23)	92 (72 - 94)	5.64
	10	05	-	15	2.57	1.43	-	4.00 (1.60 - 4.40)	1030 (290 - 1130)	4.89 (1.76 - 5.23)	92 (72 - 94)	6.01
	13	05	-	18	2.85	1.15	-	4.00 (1.60 - 4.50)	960 (290 - 1130)	4.55 (1.76 - 5.23)	92 (72 - 94)	6.45
	07	07	-	14	2.00	2.00	-	4.00 (1.60 - 4.50)	1030 (290 - 1130)	4.89 (1.76 - 5.23)	92 (72 - 94)	6.55
	10	07	-	17	2.30	1.70	-	4.00 (1.60 - 4.60)	960 (290 - 1130)	4.55 (1.76 - 5.23)	92 (72 - 94)	6.58
	13	07	-	20	2.60	1.40	-	4.00 (1.60 - 4.70)	940 (290 - 1140)	4.45 (1.76 - 5.27)	92 (72 - 94)	6.65
	10	10	-	20	2.00	2.00	-	4.00 (1.60 - 4.70)	940 (290 - 1140)	4.45 (1.76 - 5.30)	92 (72 - 94)	6.63
	13	10	-	23	2.31	1.69	-	4.00 (1.60 - 4.80)	930 (290 - 1150)	4.40 (1.76 - 5.35)	92 (72 - 94)	6.70
	13	13	-	26	2.00	2.00	-	4.00 (1.60 - 4.90)	920 (290 - 1150)	4.35 (1.76 - 5.30)	92 (72 - 94)	6.73