

Operation mode : Heating

Power supply voltage : 220V

Operating status	Indoor unit				Unit capacity (kW)			Total				
	A	B	C	ΣkBTU	A	B	C	Heating capacity (kW)	Power consumption (W)	Operating current (A)	Power factor (%)	Rated SCOP
1 unit	05	-	-	5	2.00	-	-	2.0 (0.9 - 2.5)	440 (190 - 580)	2.40 (1.20 - 2.88)	84 (72 - 92)	-
	07	-	-	7	2.70	-	-	2.7 (0.9 - 3.4)	610 (190 - 820)	3.30 (1.20 - 4.07)	84 (72 - 92)	-
	10	-	-	10	4.00	-	-	4.0 (0.9 - 4.8)	1050 (190 - 1380)	5.60 (1.20 - 6.75)	85 (72 - 93)	-
	13	-	-	13	4.40	-	-	4.4 (1.0 - 5.2)	1350 (210 - 1410)	7.14 (1.33 - 6.90)	86 (72 - 93)	-
2 units	05	05	-	10	2.00	2.00	-	4.0 (1.3 - 4.7)	920 (250 - 1270)	4.55 (1.58 - 6.15)	92 (72 - 94)	3.82
	07	05	-	12	2.70	2.00	-	4.4 (1.3 - 4.8)	960 (250 - 1270)	4.74 (1.58 - 6.15)	92 (72 - 94)	4.09
	10	05	-	15	3.73	1.87	-	4.4 (1.3 - 4.9)	960 (250 - 1270)	4.74 (1.58 - 6.15)	92 (72 - 94)	4.09
	13	05	-	18	4.00	1.60	-	4.4 (1.3 - 5.0)	950 (250 - 1250)	4.69 (1.58 - 6.05)	92 (72 - 94)	4.13
	07	07	-	14	2.70	2.70	-	4.4 (1.3 - 5.1)	960 (250 - 1270)	4.74 (1.58 - 6.15)	92 (72 - 94)	4.31
	10	07	-	17	3.34	2.26	-	4.4 (1.3 - 5.1)	950 (250 - 1250)	4.69 (1.58 - 6.05)	92 (72 - 94)	4.33
	13	07	-	20	3.64	1.96	-	4.4 (1.3 - 5.2)	920 (250 - 1250)	4.55 (1.58 - 6.05)	92 (72 - 94)	4.37
	10	10	-	20	2.80	2.80	-	4.4 (1.3 - 5.1)	930 (250 - 1230)	4.59 (1.58 - 5.95)	92 (72 - 94)	4.35
	13	10	-	23	2.30	2.10	-	4.4 (1.3 - 5.2)	910 (250 - 1230)	4.50 (1.58 - 5.95)	92 (72 - 94)	4.39
	13	13	-	26	2.20	2.20	-	4.4 (1.3 - 5.2)	890 (250 - 1220)	4.40 (1.52 - 5.90)	92 (75 - 94)	4.60

Power supply voltage : 230V

Operating status	Indoor unit				Unit capacity (kW)			Total				
	A	B	C	ΣkBTU	A	B	C	Heating capacity (kW)	Power consumption (W)	Operating current (A)	Power factor (%)	Rated SCOP
1 unit	05	-	-	5	2.00	-	-	2.0 (0.9 - 2.5)	440 (190 - 580)	2.28 (1.15 - 2.75)	84 (72 - 92)	-
	07	-	-	7	2.70	-	-	2.7 (0.9 - 3.4)	610 (190 - 820)	3.16 (1.15 - 3.90)	84 (72 - 92)	-
	10	-	-	10	4.00	-	-	4.0 (0.9 - 4.8)	1050 (190 - 1380)	5.37 (1.15 - 6.45)	85 (72 - 93)	-
	13	-	-	13	4.40	-	-	4.4 (1.0 - 5.2)	1350 (210 - 1410)	6.83 (1.27 - 6.61)	86 (72 - 93)	-
2 units	05	05	-	10	2.00	2.00	-	4.0 (1.3 - 4.7)	920 (250 - 1270)	4.34 (1.52 - 5.90)	92 (72 - 94)	3.82
	07	05	-	12	2.70	2.00	-	4.4 (1.3 - 4.8)	960 (250 - 1270)	4.53 (1.52 - 5.90)	92 (72 - 94)	4.09
	10	05	-	15	3.73	1.87	-	4.4 (1.3 - 4.9)	960 (250 - 1270)	4.53 (1.52 - 5.90)	92 (72 - 94)	4.09
	13	05	-	18	4.00	1.60	-	4.4 (1.3 - 5.0)	950 (250 - 1250)	4.48 (1.52 - 5.81)	92 (72 - 94)	4.13
	07	07	-	14	2.70	2.70	-	4.4 (1.3 - 5.1)	960 (250 - 1270)	4.53 (1.52 - 5.90)	92 (72 - 94)	4.31
	10	07	-	17	3.34	2.26	-	4.4 (1.3 - 5.1)	950 (250 - 1250)	4.48 (1.52 - 5.81)	92 (72 - 94)	4.33
	13	07	-	20	3.64	1.96	-	4.4 (1.3 - 5.2)	920 (250 - 1250)	4.34 (1.52 - 5.81)	92 (72 - 94)	4.37
	10	10	-	20	2.80	2.80	-	4.4 (1.3 - 5.1)	930 (250 - 1230)	4.39 (1.52 - 5.71)	92 (72 - 94)	4.35
	13	10	-	23	2.30	2.10	-	4.4 (1.3 - 5.2)	910 (250 - 1230)	4.29 (1.52 - 5.71)	92 (72 - 94)	4.39
	13	13	-	26	2.20	2.20	-	4.4 (1.3 - 5.2)	890 (250 - 1220)	4.20 (1.52 - 5.65)	92 (72 - 94)	4.60