

Operation mode : Heating

Power supply voltage : 230V

Operating status	Indoor unit				Unit capacity (kW)			Total				
	A	B	C	ΣkBTU	A	B	C	Heating capacity (kW)	Power consumption (W)	Operating current (A)	Power factor (%)	Rated SCOP
1 unit	05	-	-	5	2.00	-	-	2.0 (1.0 - 2.5)	460 (210 - 590)	2.35 (1.20 - 2.70)	85 (76 - 95)	-
	07	-	-	7	2.70	-	-	2.7 (1.0 - 3.4)	630 (210 - 980)	3.22 (1.20 - 4.49)	85 (76 - 95)	-
	10	-	-	10	4.00	-	-	4.0 (1.0 - 4.8)	1160 (210 - 1560)	5.37 (1.19 - 7.12)	94 (76 - 95)	-
	13	-	-	13	5.00	-	-	5.0 (1.0 - 5.3)	1580 (210 - 1770)	7.31 (1.20 - 8.10)	94 (76 - 95)	-
	16	-	-	16	5.50	-	-	5.5 (1.1 - 6.5)	1700 (230 - 2320)	7.86 (1.32 - 10.62)	94 (76 - 95)	-
2 units	05	05	-	10	2.00	2.00	-	4.0 (1.3 - 6.7)	980 (240 - 2200)	4.53 (1.36 - 10.00)	94 (77 - 96)	3.85
	07	05	-	12	2.70	2.00	-	4.7 (1.3 - 6.8)	1160 (240 - 2200)	5.37 (1.36 - 10.00)	94 (77 - 96)	3.82
	10	05	-	15	3.73	1.87	-	5.6 (1.3 - 6.9)	1380 (240 - 2100)	6.38 (1.36 - 9.55)	94 (77 - 96)	3.82
	13	05	-	18	4.00	1.60	-	5.6 (1.3 - 7.0)	1380 (240 - 2100)	6.38 (1.36 - 9.55)	94 (77 - 96)	3.82
	16	05	-	21	4.11	1.49	-	5.6 (1.3 - 7.1)	1350 (240 - 2100)	6.24 (1.36 - 9.55)	94 (77 - 96)	3.91
	07	07	-	14	2.70	2.70	-	5.0 (1.3 - 7.2)	1370 (240 - 2240)	6.34 (1.36 - 10.14)	94 (77 - 96)	4.19
	10	07	-	17	3.34	2.26	-	5.6 (1.3 - 7.2)	1390 (250 - 2200)	6.37 (1.40 - 10.00)	95 (77 - 96)	4.21
	13	07	-	20	3.64	1.96	-	5.6 (1.3 - 7.5)	1340 (250 - 2250)	6.15 (1.40 - 10.20)	95 (77 - 96)	4.32
	16	07	-	23	3.76	1.84	-	5.6 (1.3 - 7.5)	1240 (240 - 2090)	5.71 (1.36 - 9.50)	94 (77 - 96)	4.57
	10	10	-	20	2.80	2.80	-	5.6 (1.3 - 7.3)	1350 (250 - 2160)	6.20 (1.40 - 9.80)	95 (77 - 96)	4.31
	13	10	-	23	3.11	2.49	-	5.6 (1.3 - 7.5)	1320 (250 - 2210)	6.06 (1.40 - 10.05)	95 (77 - 96)	4.33
	16	10	-	26	3.24	2.36	-	5.6 (1.3 - 7.5)	1220 (240 - 2070)	5.62 (1.36 - 9.40)	94 (77 - 96)	4.59
	13	13	-	26	2.80	2.80	-	5.6 (1.3 - 7.5)	1290 (250 - 2170)	5.93 (1.40 - 9.85)	95 (77 - 96)	4.36
	16	13	-	29	2.93	2.67	-	5.6 (1.3 - 7.5)	1190 (240 - 2020)	5.48 (1.36 - 9.16)	94 (77 - 96)	4.60
	16	16	-	32	2.80	2.80	-	5.6 (1.3 - 7.5)	1140 (240 - 1910)	5.26 (1.36 - 8.65)	94 (77 - 96)	4.63

• Specification values are those under the condition as follows ;
 Heating : Capacity test condition, inside : 20 °C (Db), outside : 7 °C (Db) / 6°C (Wb)
 Piping length : 5 m per Indoor Unit.