

Operation mode : Cooling

Power supply voltage : 230V

Operating status	Indoor unit				Unit capacity (kW)			Total				
	A	B	C	ΣkBTU	A	B	C	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Power factor (%)	Rated SEER
	05	-	-	5	1.50	-	-	1.5 (1.3 - 1.8)	310 (270 - 380)	1.73 (1.52 - 1.78)	78 (77 - 93)	-
	07	-	-	7	2.00	-	-	2.0 (1.4 - 2.5)	410 (280 - 650)	2.29 (1.58 - 3.04)	78 (77 - 93)	-
	10	-	-	10	2.70	-	-	2.7 (1.4 - 3.2)	650 (280 - 890)	3.25 (1.58 - 4.12)	87 (77 - 94)	-
	13	-	-	13	3.70	-	-	3.7 (1.5 - 4.1)	1080 (280 - 1380)	5.00 (1.58 - 6.32)	94 (77 - 95)	-
	16	-	-	16	4.50	-	-	4.5 (1.6 - 5.3)	1370 (280 - 1950)	6.27 (1.58 - 8.92)	95 (77 - 95)	-
2 units	05	05	-	10	1.50	1.50	-	3.0 (2.4 - 6.0)	620 (390 - 1890)	2.87 (2.17 - 8.61)	94 (78 - 95)	-
	07	05	-	12	2.00	1.50	-	3.5 (2.4 - 6.0)	780 (390 - 1880)	3.61 (2.17 - 8.60)	94 (78 - 95)	-
	10	05	-	15	2.70	1.50	-	4.2 (2.4 - 6.0)	1050 (390 - 1890)	4.86 (2.17 - 8.59)	94 (78 - 96)	-
	13	05	-	18	3.70	1.50	-	5.2 (2.4 - 6.2)	1550 (390 - 1920)	7.09 (2.17 - 8.72)	95 (78 - 96)	-
	16	05	-	21	3.90	1.30	-	5.2 (2.4 - 6.2)	1590 (390 - 1890)	7.28 (2.17 - 8.59)	95 (78 - 96)	-
	07	07	-	14	2.00	2.00	-	4.0 (2.4 - 6.0)	970 (390 - 1890)	4.50 (2.17 - 8.61)	94 (78 - 95)	-
	10	07	-	17	2.76	1.94	-	4.7 (2.4 - 6.0)	1290 (390 - 1880)	5.93 (2.17 - 8.54)	95 (78 - 96)	-
	13	07	-	20	3.38	1.82	-	5.2 (2.4 - 6.1)	1530 (390 - 1890)	6.99 (2.17 - 8.59)	95 (78 - 96)	-
	16	07	-	23	3.62	1.58	-	5.2 (2.4 - 6.2)	1420 (390 - 1920)	6.51 (2.17 - 8.72)	95 (78 - 96)	-
	10	10	-	20	2.60	2.60	-	5.2 (2.4 - 6.1)	1570 (390 - 1890)	7.17 (2.17 - 8.59)	95 (78 - 96)	-
	13	10	-	23	2.94	2.26	-	5.2 (2.4 - 6.0)	1520 (390 - 1900)	6.95 (2.17 - 8.63)	95 (78 - 96)	-
	16	10	-	26	3.20	2.00	-	5.2 (2.4 - 6.3)	1410 (390 - 1920)	6.46 (2.17 - 8.72)	95 (78 - 96)	-
	13	13	-	26	2.60	2.60	-	5.2 (2.4 - 6.1)	1450 (390 - 1920)	6.73 (2.17 - 8.72)	94 (78 - 96)	-
	16	13	-	29	2.87	2.33	-	5.2 (2.4 - 6.2)	1380 (390 - 1930)	6.33 (2.17 - 8.76)	95 (78 - 96)	-
	16	16	-	32	2.60	2.60	-	5.2 (2.4 - 6.4)	1340 (390 - 1950)	6.15 (2.17 - 8.85)	95 (78 - 96)	-

* Specification values are those under the condition as follows ;

Cooling : Capacity test condition, inside : 27 °C (Db) / 19 °C (Wb), outside : 35 °C (Db) / 24 °C (Wb)

Piping length : 5 m. per indoor unit.

Operation mode : Cooling

Power supply voltage : 230V

Operating status	Indoor unit				Unit capacity (kW)			Total				
	A	B	C	ΣkBTU	A	B	C	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Power factor (%)	Rated SEER
3 units	05	05	05	15	1.50	1.50	1.50	4.5 (2.4 - 6.3)	1130 (400 - 1890)	5.23 (2.22 - 8.58)	94 (78 - 96)	6.35
	07	05	05	17	2.00	1.50	1.50	5.0 (2.4 - 6.4)	1390 (400 - 1890)	6.43 (2.22 - 8.58)	94 (78 - 96)	5.74
	10	05	05	20	2.46	1.37	1.37	5.2 (2.4 - 6.5)	1530 (400 - 1890)	7.08 (2.22 - 8.58)	94 (78 - 96)	5.42
	13	05	05	23	2.87	1.16	1.16	5.2 (2.4 - 6.5)	1210 (400 - 1950)	5.60 (2.22 - 8.85)	94 (78 - 96)	6.85
	16	05	05	26	3.12	1.04	1.04	5.2 (2.4 - 6.5)	1200 (400 - 1950)	5.55 (2.22 - 8.85)	94 (78 - 96)	6.91
	07	07	05	19	1.89	1.89	1.42	5.2 (2.4 - 6.5)	1560 (400 - 1950)	7.22 (2.22 - 8.85)	94 (78 - 96)	5.32
	10	07	05	22	2.26	1.68	1.26	5.2 (2.4 - 6.5)	1220 (400 - 1950)	5.64 (2.22 - 8.85)	94 (78 - 96)	6.80
	13	07	05	25	2.67	1.44	1.08	5.2 (2.4 - 6.5)	1410 (400 - 1950)	6.52 (2.22 - 8.85)	94 (78 - 96)	5.88
	16	07	05	28	2.93	1.30	0.98	5.2 (2.4 - 6.5)	1190 (400 - 1950)	5.50 (2.22 - 8.85)	94 (78 - 96)	6.97
	10	10	05	25	2.03	2.03	1.13	5.2 (2.4 - 6.5)	1210 (400 - 1950)	5.60 (2.22 - 8.85)	94 (78 - 96)	6.85
	13	10	05	28	2.44	1.78	0.99	5.2 (2.4 - 6.5)	1200 (400 - 1950)	5.55 (2.22 - 8.85)	94 (78 - 96)	6.91
	16	10	05	31	2.69	1.61	0.90	5.2 (2.4 - 6.5)	1190 (400 - 1950)	5.50 (2.22 - 8.85)	94 (78 - 96)	6.97
	13	13	05	31	2.16	2.16	0.88	5.2 (2.4 - 6.5)	1180 (400 - 1950)	5.46 (2.22 - 8.85)	94 (78 - 96)	7.03
	16	13	05	34	2.41	1.98	0.80	5.2 (2.4 - 6.5)	1170 (400 - 1950)	5.41 (2.22 - 8.85)	94 (78 - 96)	7.09
	07	07	07	21	1.74	1.73	1.73	5.2 (2.4 - 6.5)	1220 (400 - 1950)	5.62 (2.22 - 8.85)	94 (78 - 96)	6.92
	10	07	07	24	2.17	1.52	1.52	5.2 (2.4 - 6.5)	1210 (400 - 1950)	5.57 (2.22 - 8.85)	94 (78 - 96)	6.91
	13	07	07	27	2.50	1.35	1.35	5.2 (2.4 - 6.5)	1200 (400 - 1950)	5.53 (2.22 - 8.85)	94 (78 - 96)	6.90
	16	07	07	30	2.78	1.21	1.21	5.2 (2.4 - 6.5)	1190 (400 - 1950)	5.48 (2.22 - 8.85)	94 (78 - 96)	6.84
	10	10	07	27	1.93	1.93	1.34	5.2 (2.4 - 6.5)	1200 (400 - 1950)	5.53 (2.22 - 8.85)	94 (78 - 96)	6.91
	13	10	07	30	2.25	1.73	1.21	5.2 (2.4 - 6.5)	1190 (400 - 1950)	5.48 (2.22 - 8.85)	94 (78 - 96)	6.89
	16	10	07	33	2.52	1.58	1.10	5.2 (2.4 - 6.5)	1180 (400 - 1950)	5.44 (2.22 - 8.85)	94 (78 - 96)	6.82
	13	13	07	33	2.05	2.05	1.09	5.2 (2.4 - 6.5)	1180 (400 - 1950)	5.44 (2.22 - 8.85)	94 (78 - 96)	6.87
	16	13	07	36	2.31	1.88	1.01	5.2 (2.4 - 6.5)	1170 (400 - 1950)	5.39 (2.22 - 8.85)	94 (78 - 96)	6.75
	10	10	10	30	1.74	1.73	1.73	5.2 (2.4 - 6.5)	1190 (400 - 1950)	5.48 (2.22 - 8.85)	94 (78 - 96)	6.90
	13	10	10	33	2.06	1.58	1.58	5.2 (2.4 - 6.5)	1180 (400 - 1950)	5.44 (2.22 - 8.85)	94 (78 - 96)	6.87
	16	10	10	36	2.31	1.44	1.44	5.2 (2.4 - 6.5)	1170 (400 - 1950)	5.39 (2.22 - 8.85)	94 (78 - 96)	6.80
	13	13	10	36	1.88	1.88	1.45	5.2 (2.4 - 6.5)	1170 (400 - 1950)	5.39 (2.22 - 8.85)	94 (78 - 96)	6.85

* Specification values are those under the condition as follows ;

Cooling : Capacity test condition, inside : 27 °C (Db) / 19 °C (Wb), outside : 35 °C (Db) / 24 °C (Wb)

Piping length : 5 m. per indoor unit.